



ShortDipole

UPM Raflatac ShortDipole^x

Protocol

EPC Class 1 Gen 2

Operating frequency

Global 860–960 MHz

Antenna size

92 x 11 mm /

3.6 x 0.4 inch

ShortDipole^x key features

- Cost-efficient, high performance product for global supply chain management.
- ShortDipole^x is suitable for corrugated materials and plastics.
- Wal-Mart, DoD and METRO Group compliant inlay.
- Typically converted into 4x6" labels.
- For pallets, cases and item-level use.
- Up to 240-bit EPC memory.
- 64-bit tag identifier (TID) including 32-bit unique serial number.

UPM Raflatac ShortDipole^x



RoHS



Antenna dimensions

Antenna size	92 x 11 mm / 3.62 x 0.43"
Die-cut size	97 x 15 mm / 3.82 x 0.59"
Web width	100 mm / 3.94"

Electrical specifications

IC	NXP U-Code G2XL/G2XM
EPC memory	up to 240 bit
User memory	up to 512 bit
Operating frequency	860–960 MHz

General characteristics of inlay


Operating temperature	-40 °C to 85 °C -40 °F to 185 °F
Bending diameter (D)	> 50 mm tension max. 10 N
Static pressure (P)	<10 MPa

Delivery formats



Available formats	Dry, wet, tag
Adhesive – temperature	Solvent-free permanent adhesive min. -10 °C to 120 °C min. 14 °F to 248 °F
Quality	100% performance tested

Reel details

Standard reel size	10,000 dry or wet inlays / 5,000 tags
--------------------	--



Inner core diameter 76 mm / 3 inch



All the graphs are indicative: performance in real life applications may vary. The data has been determined based on calculations for transmitters with a 2W ERP output power level.

UPM Raflatac uses three different test methods to evaluate the reliability of the RFID inlay and tag products it produces. Products are tested according to IEC 60068-2-67 (temperature and humidity), JESD22-A104-B (temperature cycling) and an in-house developed bending test.

Disclaimer

UPM Raflatac reserves the right to change its products and services at any time without notice. Our recommendations are based on our latest knowledge and experience. As our products are used in circumstances beyond our control, we cannot be held liable for any damage caused through their use.

